



Waterbased Media Technical Data Sheets



FUJIFILM Professional Cut Sheet Media

• High Gloss Photo Paper 280gsm	Page 5
• Satin Photo Paper 280gsm	Page 6
• Fine Art Museum Baryte Paper 300gsm	Page 7
• Fine Art Fibre Baryte Gloss Paper 310gsm	Page 8
• Fine Art Baryte Matt BW Paper 310gsm	Page 9
• Fine Art Etch Paper 300gsm	Page 10
• Fine Art Photo Rag Paper 300gsm	Page 11

FUJIFILM Roll Media

• Glossy Paper 200gsm	Page 13
• Lustre Paper 200gsm	Page 14
• Photo Paper Glossy 240gsm	Page 15
• Premium Lustre Paper 245gsm	Page 16
• Photo Paper Satin 270gsm	Page 17
• Pearl Photo Paper 290gsm	Page 18
• Fine Art Museum Baryte Paper 300gsm	Page 19
• Fine Art Fibre Baryte Gloss 310 gsm	Page 20
• Fine Art Fibre Baryte Matt BW 310 gsm	Page 21
• Fine Art Etch Paper 300gsm	Page 22
• Fine Art Photo Rag Paper 300gsm	Page 23
• Fine Art Museum Smooth Rag Paper 300gsm	Page 24
• Fine Art Museum Rough Paper 300gsm	Page 25
• Fine Art Museum Torchon Paper 300gsm	Page 26
• Fine Art Museum Canvas Paper 300gsm	Page 27
• Artist Canvas 340gsm	Page 28
• HD White Cotton Canvas 400gsm	Page 29
• Fine Art Natural Canvas 390gsm	Page 30
• Satin Canvas 350gsm	Page 31
• Smooth White Canvas 350gsm	Page 32
• Premium Matt Bond Paper 90gsm	Page 33
• Premium Matt Bond Paper 120gsm	Page 34
• Premium Matt Bond Paper 180gsm	Page 35
• Pop-Up Banner 190μ	Page 36
• Satin Adhesive Vinyl 175μ	Page 37



Technical Data Sheets Professional Sheet Media

High Gloss Photo Paper 280GSM



Product Description

FUJIFILM's High Gloss Photo Paper is a fast drying high gloss resin coated paper for photo realistic image processing.

Surface Smooth gloss surface

Weight 280 gsm

Caliper 280 micron (11 mil)

Opacity 99%

Gloss (20°) 42%

Tint (Lab) 96.0, 0.2, -4.7

Printer Compatibility All piezo and thermal inkjet printers

Ink Compatibility Aqueous pigment or dye*

Handling Recommendations Use gloves when handling media. Before finishing, allow approximately 24 hours for total drying.

Storage & Use Recommendations Product should be stored under cool, dry conditions in its original packaging.
 Temperature: 10-30° C
 Relative Humidity: 20-60%

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

Formats

SIZE	QUANTITY	CAT NR.
A4	50 sheets	998948
A4	300 sheets	985606
A3+	50 sheets	998955

NOTE: Information provided for guidance only and can change without notice.

SATIN PHOTO PAPER 280GSM



Product Description

FUJIFILM's Satin Photo Paper is a fast drying satin surface resin coated paper for photo realistic image processing. Scratch resistant coating.

Surface Smooth satin surface

Weight 280 gsm

Caliper 280 micron (11 mil)

Opacity 99%

Gloss (60°) 24%

Tint (Lab) 96.0, 0.2, -4.7

Printer Compatibility All piezo and thermal inkjet printers

Ink Compatibility Aqueous pigment or dye*

Handling Recommendations Use gloves when handling media. Before finishing, allow approximately 24 hours for total drying.

Storage & Use Recommendations Product should be stored under cool, dry conditions in its original packaging.
 Temperature: 10-30° C
 Relative Humidity: 20-60%

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

Formats

SIZE	QUANTITY	CAT NR.
A4	50 sheets	998963
A4	300 sheets	985614
A3+	50 sheets	998971

FINE ART MUSEUM BARYTE PAPER 300GSM



Product Description	FUJIFILM's Fine Art Museum Baryte Paper is a baryte paper with semi-gloss slightly structured finish.
Surface	Single side coated with gloss ink receptive coating
Weight	300 gsm
Caliper	325 micron
Opacity	99%
Gloss	N/A
Tint (Lab)	96, 1.4, -3.5
Printer Compatibility	All piezo and thermal inkjet printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for total drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25° C Relative Humidity: 40-60%

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

Formats	SIZE	QUANTITY	CAT NR.
	A3+	40 sheets	998997
	A2	40 sheets	998989

NOTE: Information provided for guidance only and can change without notice.

FINE ART FIBRE BARYTE GLOSS PAPER 310GSM



Product Description

FUJIFILM's Fine Art Fibre Baryte Gloss is a second generation high quality real Baryte paper with bright white gloss finish. Perfect for professional and exhibition prints. The baryta is in the paper base giving excellent colour rendition. Looks and feels like a traditional photo paper.

Surface

Gloss

Weight

310 gsm

Caliper

327 micron

Opacity

99.05 - 99.45 %

Gloss

13.93% at 20 degrees, 44.36% at 60 degrees, and 75.6% at 85 degrees

Tint (Lab)

98.63, 0.51, -2.46

Printer Compatibility

All piezo and thermal inkjet printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for total drying.

Storage & Use Recommendations:

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-30° C

Relative Humidity: 20-60%

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

Formats

SIZE	QUANTITY	CAT NR.
A4	50 sheets	998641
A3+	50 sheets	998658
A2	50 sheets	998666

NOTE: Information provided for guidance only and can change without notice.

FINE ART FIBRE BARYTE MATT BW PAPER 310GSM



Product Description

FUJIFILM's Fine Art Fibre Baryte Matt BW Paper is a second generation real Baryte paper with a matt surface and warm base. Ideal for Black & White images and for high quality portraiture and exhibition prints.

Surface

Matt

Weight

310 gsm

Caliper

310 micron (12 mil)

Opacity

99,4 – 99,8%

Gloss

1.3% at 20 degrees, 2.5% at 60 degrees, and 5% at 85 degrees

Tint (Lab)

98.02, 1.66, -4.01

Printer Compatibility

All piezo and thermal inkjet printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for total drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-30° C

Relative Humidity: 20-60%

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

Formats

SIZE	QUANTITY	CAT NR.
A4	50 sheets	998674
A3+	50 sheets	998682
A2	50 sheets	998690

NOTE: Information provided for guidance only and can change without notice.

FINE ART ETCH PAPER

300GSM



Product Description

FUJIFILM's Fine Art Etch Paper is a mould-made, traditional fine art paper with a special matt coating. It has a very mild structured surface and is acid free. Ideal for high quality digital fine art reproductions.

Surface

Single side coated with matt ink receptive coating

Weight

300 gsm

Caliper

500 micron

Opacity

99%

Gloss

N/A

Tint (Lab)

96.57, 0.86, 0.65

Printer Compatibility

All piezo and thermal inkjet printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for total drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.
 Temperature: 10-30° C
 Relative Humidity: 20-60%

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

Formats

SIZE	QUANTITY	CAT NR.
A4	30 sheets	999036
A3+	30 sheets	999030

FINE ART PHOTO RAG PAPER 300GSM



Product Description

FUJIFILM's Fine Art Photo Rag Paper is a cotton 100% rag traditional fine art paper with a special smooth matt coating. This is a top of the range rag paper with a firm 300g base. Ideal for high quality digital fine art reproductions.

Surface

Single side coated with matt ink receptive coating

Weight

300 gsm

Caliper

480 micron

Opacity

99%

Gloss

N/A

Tint (Lab)

96.62, 0.90, -0.32

Printer Compatibility

All piezo and thermal inkjet printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for total drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-30° C

Relative Humidity: 20-60%

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

Formats

SIZE	QUANTITY	CAT NR.
A4	30 sheets	999011
A3+	30 sheets	999004
A2	30 sheets	999145

NOTE: Information provided for guidance only and can change without notice.



Technical Data Sheets Roll Media

GLOSSY PAPER 200GSM



Product Description	FUJIFILM's Glossy Paper is a instant dry resin coated glossy paper gives excellent colour reproduction with smooth, rich tones.												
Surface	Single side coated with matt ink receptive coating												
Weight	200 gsm												
Caliper	205 micron (8 mil)												
Opacity	>98%												
Gloss (20°)	>30%												
Tint (Lab)	95.0, 0.75, -4.75												
Printer Compatibility	Compatible with most Photo-capable desktop printers												
Ink Compatibility	Aqueous pigment or dye*												
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.												
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 10-50° C Relative Humidity: 10-80%												
Formats	<table border="1"> <thead> <tr> <th>SIZE</th> <th>CORE</th> <th>PAPER LENGTH</th> <th>CAT NR.</th> </tr> </thead> <tbody> <tr> <td>610 mm (24")</td> <td>2"</td> <td>30m</td> <td>996330</td> </tr> <tr> <td>1118 mm (44")</td> <td>2"</td> <td>30m</td> <td>996348</td> </tr> </tbody> </table>	SIZE	CORE	PAPER LENGTH	CAT NR.	610 mm (24")	2"	30m	996330	1118 mm (44")	2"	30m	996348
SIZE	CORE	PAPER LENGTH	CAT NR.										
610 mm (24")	2"	30m	996330										
1118 mm (44")	2"	30m	996348										

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

LUSTRE PAPER 200GSM



Product Description

FUJIFILM's Lustre Paper is a instant dry resin coated lustre paper gives excellent colour reproduction with smooth, rich tones.

Surface

Single side coated with matt ink receptive coating

Weight

200 gsm

Caliper

210 micron (8 mil)

Opacity

>98%

Gloss (60°)

>22%

Tint (Lab)

95.0, 0.75, -4.75

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-50° C

Relative Humidity: 10-80%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	2"	30m	996355
1118 mm (44")	2"	30m	996363
1524 mm (60")	2"	30m	998211

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

PHOTO PAPER GLOSSY

240GSM



Product Description

FUJIFILM's Photo Paper Glossy is an instant dry, high gloss photo base paper with Fujifilm's Luminax technology. It has an exceptionally white base and high gloss with a very even surface.

Surface

Single side coated with matt ink receptive coating

Weight

240 gsm

Caliper

235 micron

Opacity

96,20%

Gloss (60°)

35%

Tint (Lab)

94.7, 1.0, -8.2

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 0-30°C

Relative Humidity: 20-80%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
305 mm (12")	3"	30m	989822
406 mm (16")	3"	30m	989830
432 mm (17")	3"	30m	989491
508 mm (20")	3"	30m	938837
610 mm (24")	3"	30m	989509
915 mm (36")	3"	30m	989517
1118 mm (44")	3"	30m	989525

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

PREMIUM LUSTRE PAPER

245GSM



Product Description

FUJIFILM's Premium Lustre Paper is a high white, medium weight premium lustre paper with a robust surface for easy handling.

Surface

Single side coated with matt ink receptive coating

Weight

245 gsm

Caliper

255 micron (10 mil)

Opacity

>98%

Gloss (60°)

>20%

Tint (Lab)

95.5, 2.45, -8.3

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-30° C

Relative Humidity: 10-80%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	2"	30m	999524
1118 mm (44")	2"	30m	999532
1524 mm (60")	2"	30m	999540

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

PHOTO PAPER SATIN

270GSM



Product Description	FUJIFILM's Photo Paper Satin is a Fast drying satin surface resin coated paper for photo realistic image processing. The base is very similar to a classic silver halide photo base.
Surface	Single side coated with matt ink receptive coating
Weight	270 gsm
Caliper	280 micron
Opacity	97,50%
Gloss (60°)	35%
Tint (Lab)	94.6, -0.1, -3.6
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 0-30°C Relative Humidity: 20-80%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
305 mm (12")	3"	30m	996033
406 mm (16")	3"	30m	996041
432 mm (17")	3"	30m	996058
508 mm (20")	3"	30m	938829
610 mm (24")	3"	30m	996066
915 mm (36")	3"	30m	996074
1118 mm (44")	3"	30m	996082

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

PEARL PHOTO PAPER

290GSM



Product Description

FUJIFILM's Pearl Photo Paper is a fast drying robust pearl surface with mild structure and a robust protective coating resistant to scratching and marking making it very easy to handle in shop and lab environments. A premium level paper.

Surface

Single side coated with matt ink receptive coating

Weight

290 gsm

Caliper

280 micron (11mil)

Opacity

>99%

Gloss (60°)

24%

Tint (Lab)

96.0, 0.2, -4.7

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-50°C

Relative Humidity: 10-80%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
406 mm (16")	3"	30m	996314
432 mm (17")	3"	30m	999408
610 mm (24")	3"	30m	996710
1118 mm (44")	3"	30m	996322
1524 mm (60")	3"	30m	998229

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

FINE ART MUSEUM BARYTE PAPER 300GSM



Product Description	FUJIFILM's Fine Art Museum Baryte Paper is a baryte paper with semi-gloss slightly structured finish.
Surface	Single side coated with matt ink receptive coating
Weight	300 gsm
Caliper	325 micron
Opacity	99%
Gloss (60°)	N/A
Tint (Lab)	96, 1.4, -3.5
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 40-60%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
432 mm (17")	3"	15m	995373
610 mm (24")	3"	15m	995381
1118 mm (44")	3"	15m	995399
1524 mm (60")	3"	15m	998203

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

FINE ART FIBRE BARYTE

GLOSS 310GSM



Product Description

FUJIFILM's Fine Art Fibre Baryte Gloss is a Second generation high quality real Baryte paper with bright white gloss finish. Perfect for professional and exhibition prints. The baryta is in the paper base giving excellent colour rendition. Looks and feels like a traditional photo paper.

Surface Single side coated with matt ink receptive coating

Weight 320 gsm

Caliper 327 micron

Opacity 99%

Gloss (60°) 44.36%

Tint (Lab) 98.63, 0.51, -2.46

Printer Compatibility Compatible with most Photo-capable desktop printers

Ink Compatibility Aqueous pigment or dye*

Handling Recommendations Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations Product should be stored under cool, dry conditions in its original packaging.

Temperature: 20-30°C

Relative Humidity: 30-50%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	3"	15m	998609
1118 mm (44")	3"	15m	998617

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

FINE ART FIBRE BARYTE MATT 310GSM



Product Description

FUJIFILM's Fine Art Fibre Baryte Matt is a second generation real Baryte paper with a matt surface and warm base. Ideal for Black & White images and for high quality portraiture and exhibition prints.

Surface

Single side coated with matt ink receptive coating

Weight

310 gsm

Caliper

310 micron (12mil)

Opacity

99%

Gloss (60°)

2.5%

Tint (Lab)

98.02, 1.66, -4.01

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 20-30°C

Relative Humidity: 30-50%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	3"	15m	998625
1118 mm (44")	3"	15m	998633

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

FINE ART ETCH PAPER

300GSM



Product Description

FUJIFILM's Fine Art Etch Paper is a mould-made, traditional fine art paper with a special matt coating. It has a very mild structured surface and is acid free. Ideal for high quality digital fine art reproductions.

Surface

Single side coated with matt ink receptive coating

Weight

310 gsm

Caliper

510 micron

Opacity

99%

Gloss (60°)

N/A

Tint (Lab)

96.57, 0.86, 0.65

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-30°C

Relative Humidity: 35-65%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
432 mm (17")	3"	12m	991729
610 mm (24")	3"	12m	986778
915 mm (36")	3"	12m	986786
1118 mm (44")	3"	12m	986794

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

FINE ART PHOTO RAG PAPER 300GSM



Product Description

FUJIFILM's Fine Art Photo Rag Paper is a cotton 100% rag traditional fine art paper with a special smooth matt coating. This is a top of the range rag paper with a firm 300g base. Ideal for high quality digital fine art reproductions.

Surface

Single side coated with matt ink receptive coating

Weight

308 gsm

Caliper

450 micron

Opacity

99%

Gloss (60°)

N/A

Tint (Lab)

96.62, 0.90, -0.32

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.

Temperature: 10-30°C

Relative Humidity: 35-65%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
432 mm (17")	3"	12m	991737
610 mm (24")	3"	12m	986802
1118 mm (44")	3"	12m	986810

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

FINE ART MUSEUM SMOOTH RAG PAPER 300GSM



Product Description	FUJIFILM's Fine Art Museum Smooth Rag Paper is a 100% cotton rag media has a smooth coating to accurately reproduce fine art images. Top quality for the price.												
Surface	Single side coated with matt ink receptive coating												
Weight	315 gsm												
Caliper	390 micron												
Opacity	99%												
Gloss (60°)	N/A												
Tint (Lab)	96.2, 0.7, 0.0												
Printer Compatibility	Compatible with most Photo-capable desktop printers												
Ink Compatibility	Aqueous pigment or dye*												
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.												
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 40-60%												
Formats	<table border="1"> <thead> <tr> <th>SIZE</th> <th>CORE</th> <th>PAPER LENGTH</th> <th>CAT NR.</th> </tr> </thead> <tbody> <tr> <td>610 mm (24")</td> <td>3"</td> <td>15m</td> <td>995357</td> </tr> <tr> <td>1118 mm (44")</td> <td>3"</td> <td>15m</td> <td>995365</td> </tr> </tbody> </table>	SIZE	CORE	PAPER LENGTH	CAT NR.	610 mm (24")	3"	15m	995357	1118 mm (44")	3"	15m	995365
SIZE	CORE	PAPER LENGTH	CAT NR.										
610 mm (24")	3"	15m	995357										
1118 mm (44")	3"	15m	995365										

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

FINE ART MUSEUM ROUGH PAPER 300GSM



Product Description	FUJIFILM's Fine Art Museum Rough Paper is a Cotton based heavy weight paper ideal for fine art images. A special finish thanks to the rough structure.												
Surface	Single side coated with matt ink receptive coating												
Weight	315 gsm												
Caliper	460 micron												
Opacity	99%												
Gloss (60°)	N/A												
Tint (Lab)	96.7, 0.0, 2.9												
Printer Compatibility	Compatible with most Photo-capable desktop printers												
Ink Compatibility	Aqueous pigment or dye*												
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.												
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 40-60%												
Formats	<table border="1"> <thead> <tr> <th>SIZE</th> <th>CORE</th> <th>PAPER LENGTH</th> <th>CAT NR.</th> </tr> </thead> <tbody> <tr> <td>610 mm (24")</td> <td>3"</td> <td>15m</td> <td>989913</td> </tr> <tr> <td>1118 mm (44")</td> <td>3"</td> <td>15m</td> <td>989905</td> </tr> </tbody> </table>	SIZE	CORE	PAPER LENGTH	CAT NR.	610 mm (24")	3"	15m	989913	1118 mm (44")	3"	15m	989905
SIZE	CORE	PAPER LENGTH	CAT NR.										
610 mm (24")	3"	15m	989913										
1118 mm (44")	3"	15m	989905										

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

FINE ART MUSEUM TORCHON PAPER 300GSM



Product Description	FUJIFILM's Fine Art Museum Torchon Paper is a Cotton based heavy weight paper ideal for fine art images. A special torchon top structure ideal for art images.
Surface	Single side coated with matt ink receptive coating
Weight	315 gsm
Caliper	520 micron
Opacity	99%
Gloss (60°)	N/A
Tint (Lab)	96.7, -0.1, 3.7
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 40-60%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	3"	15m	989897
1118 mm (44")	3"	15m	989889

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

FINE ART MUSEUM CANVAS PAPER 300GSM



Product Description FUJIFILM's Fine Art Museum Canvas Paper is a paper with a Canvas look surface.

Surface Single side coated with matt ink receptive coating

Weight 300 gsm

Caliper 370 micron

Opacity 99%

Gloss (60°) N/A

Tint (Lab) 96.2, 0.0, 3.3

Printer Compatibility Compatible with most Photo-capable desktop printers

Ink Compatibility Aqueous pigment or dye*

Handling Recommendations Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations Product should be stored under cool, dry conditions in its original packaging.
Temperature: 15-25°C
Relative Humidity: 40-60%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	3"	15m	992610
1118 mm (44")	3"	15m	992602

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

ARTIST CANVAS 340GSM



Product Description

FUJIFILM's Artist Canvas is our top of the range poly-cotton canvas with a real canvas look and feel. Ideal for reproductions of paintings and to give added value to artwork.

Surface

Single side coated with matt ink receptive coating

Weight

340 gsm

Caliper

520 micron

Opacity

92%

Gloss (60°)

<5%

Tint (Lab)

94.7, 0.1, 2.2

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Storage & Use Recommendations

Product should be stored under cool, dry conditions in its original packaging.
 Temperature: 10-30°C
 Relative Humidity: 35-65%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
432 mm (17")	2"	20m	991711
610 mm (24")	2"	12m	977405
915 mm (36")	2"	12m	997676
1118 mm (44")	2"	12m	977421
1524 mm (60")	2"	12m	998187

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.



HD WHITE COTTON CANVAS

400GSM

Product Description	FUJIFILM's HD White Cotton Canvas is a 400g pure cotton canvas coated for inkjet with a high intensity white surface. Perfect for photographic images.
Surface	Single side coated with matt ink receptive coating
Weight	415 gsm
Caliper	490 micron
Opacity	90%
Gloss (60°)	2%
Tint (Lab)	96.6, 1.9, -6.5
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 10-30°C Relative Humidity: 35-65%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
432 mm (17")	2"	12m	995555
610 mm (24")	2"	12m	995530
1118 mm (44")	2"	12m	995548
1524 mm (60")	2"	12m	998195

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

FINE ART NATURAL CANVAS 390GSM



Product Description	FUJIFILM's Fine Art Natural Canvas is a 390g pure cotton canvas coated for inkjet - ideal for canvas frames.
Surface	Single side coated with matt ink receptive coating
Weight	390 gsm
Caliper	600 micron
Opacity	96%
Gloss (60°)	<5%
Tint (Lab)	92.3, 1.9, 2.1
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 10-30°C Relative Humidity: 35-65%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	2"	12m	998591
1118 mm (44")	2"	12m	998583

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

SATIN CANVAS 350GSM



Product Description	FUJIFILM's Satin Canvas is a poly-cotton satin finish canvas coated for inkjet - a very popular new finish.
Surface	Single side coated with matt ink receptive coating
Weight	350 gsm
Caliper	475 micron
Opacity	93%
Gloss (60°)	7%
Tint (Lab)	93.4, 0.2, 2.4
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 10-30°C Relative Humidity: 35-65%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	2"	12m	998930
1118 mm (44")	2"	12m	998922

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

SMOOTH WHITE CANVAS

350GSM



Product Description	FUJIFILM's Smooth White Canvas is a 350g poly-cotton canvas with a smooth textured surface and bright white.
Surface	Single side coated with matt ink receptive coating
Weight	350 gsm
Caliper	400 micron
Opacity	99%
Gloss (60°)	N/A
Tint (Lab)	94.2, 1.5, -5.2
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 10-30°C Relative Humidity: 35-65%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	3"	15m	999565
1118 mm (44")	3"	15m	999568

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

PREMIUM MATT BOND PAPER 90GSM



Product Description	FUJIFILM's Premium Matt Bond Paper will gradually replace current range of Matt Bond. Same coating used on all weights for consistency.								
Surface	Single side coated with matt ink receptive coating								
Weight	90 gsm								
Caliper	113 micron								
Opacity	89%								
Gloss (60°)	N/A								
Tint (Lab)	96.5, 3.9, -14.5								
Printer Compatibility	Compatible with most Photo-capable desktop printers								
Ink Compatibility	Aqueous pigment or dye*								
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.								
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 30-70%								
Formats	<table border="1"> <thead> <tr> <th>SIZE</th> <th>CORE</th> <th>PAPER LENGTH</th> <th>CAT NR.</th> </tr> </thead> <tbody> <tr> <td>1067 mm (42")</td> <td>2"</td> <td>45m</td> <td>986753</td> </tr> </tbody> </table>	SIZE	CORE	PAPER LENGTH	CAT NR.	1067 mm (42")	2"	45m	986753
SIZE	CORE	PAPER LENGTH	CAT NR.						
1067 mm (42")	2"	45m	986753						

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

PREMIUM MATT BOND PAPER 120GSM



Product Description	FUJIFILM's Premium Matt Bond Paper will gradually replace current range of Matt Bond. Same coating used on all weights for consistency.								
Surface	Single side coated with matt ink receptive coating								
Weight	120 gsm								
Caliper	150 micron								
Opacity	93%								
Gloss (60°)	N/A								
Tint (Lab)	97, 3.9, -14.5								
Printer Compatibility	Compatible with most Photo-capable desktop printers								
Ink Compatibility	Aqueous pigment or dye*								
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.								
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 30-70%								
Formats	<table border="1"> <thead> <tr> <th>SIZE</th> <th>CORE</th> <th>PAPER LENGTH</th> <th>CAT NR.</th> </tr> </thead> <tbody> <tr> <td>1067 mm (42")</td> <td>2"</td> <td>30m</td> <td>986754</td> </tr> </tbody> </table>	SIZE	CORE	PAPER LENGTH	CAT NR.	1067 mm (42")	2"	30m	986754
SIZE	CORE	PAPER LENGTH	CAT NR.						
1067 mm (42")	2"	30m	986754						

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.

PREMIUM MATT BOND PAPER 180GSM



Product Description	FUJIFILM's Premium Matt Bond Paper will gradually replace current range of Matt Bond. Same coating used on all weights for consistency.
Surface	Single side coated with matt ink receptive coating
Weight	180 gsm
Caliper	229 micron
Opacity	97%
Gloss (60°)	N/A
Tint (Lab)	97, 3.7, -14.5
Printer Compatibility	Compatible with most Photo-capable desktop printers
Ink Compatibility	Aqueous pigment or dye*
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 30-70%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
432 mm (17")	2"	30m	998238
610 mm (24")	2"	30m	998239
915 mm (36")	2"	30m	998240
1118 mm (44")	2"	30m	998241

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

POP-UP BANNER 190 μ



Product Description	FUJIFILM's Pop-Up Banner is a special high gloss banner material ideal for 'pop-up' stands with backstop coating .												
Surface	Single side coated with matt ink receptive coating												
Weight	230 gsm												
Caliper	190 micron												
Opacity	>99%												
Gloss (20°)	14%												
Tint (Lab)	95.0, 0.5, -5.5												
Printer Compatibility	Compatible with most Photo-capable desktop printers												
Ink Compatibility	Aqueous pigment or dye*												
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.												
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging. Temperature: 15-25°C Relative Humidity: 30-70%												
Formats	<table border="1"> <thead> <tr> <th>SIZE</th> <th>CORE</th> <th>PAPER LENGTH</th> <th>CAT NR.</th> </tr> </thead> <tbody> <tr> <td>610 mm (24")</td> <td>2"</td> <td>30m</td> <td>992594</td> </tr> <tr> <td>915 mm (36")</td> <td>2"</td> <td>30m</td> <td>989301</td> </tr> </tbody> </table>	SIZE	CORE	PAPER LENGTH	CAT NR.	610 mm (24")	2"	30m	992594	915 mm (36")	2"	30m	989301
SIZE	CORE	PAPER LENGTH	CAT NR.										
610 mm (24")	2"	30m	992594										
915 mm (36")	2"	30m	989301										

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

SATIN ADHESIVE VINYL 175 μ

FUJIFILM



Product Description

FUJIFILM's Satin Adhesive Vinyl is a fast drying satin surfaced adhesive vinyl for short term unprotected outdoor use. Specially designed for photo realistic image processing.

Surface

Single side coated with matt ink receptive coating

Weight

N/A

Caliper

300 micron

Opacity

99%

Gloss (60°)

N/A

Tint (Lab)

96.8, 0.0, 3.3

Printer Compatibility

Compatible with most Photo-capable desktop printers

Ink Compatibility

Aqueous pigment or dye*

Handling

Use gloves when handling media. Before finishing, allow approximately 24 hours for drying.

Recommendations

Storage & Use

Product should be stored under cool, dry conditions in its original packaging.

Recommendations

Temperature: 10-20°C

Relative Humidity: 40-50%

Formats

SIZE	CORE	PAPER LENGTH	CAT NR.
610 mm (24")	2"	20m	978940

* Use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

NOTE: Information provided for guidance only and can change without notice.