

Color+ Series QJ

Solvent-based Inkjet Inks



PRODUCT INFORMATION

Color+ Series QJ inks have been designed specifically for Turbojet printers or similar drop on demand inkjet printers.

Features

- Solvent-based technology
- Fast drying
- Bright vibrant colours
- Suitable for uncoated materials
- Recommended for both internal & external applications

Ink Properties

Color+ Series QJ is a range of high density, highly durable solvent-based pigmented inks for use with the Scitex Turbojet. The inks are designed to ensure easy switchover from the OEM inks.

Using the best quality pigments and Fujifilm's unique Micro V dispersion technology, Color+ Series QJ inks provide a wider, cleaner colour gamut increasing the number of colours achievable.

Colour Range

QJ004	Black	(±)
QJ052	Yellow	(±)
QJ135	Magenta	(±)
QJ185	Light Magenta	(±)
QJ215	Cyan	(±)
QJ255	Light Cyan	(±)
QU016	Flushing and Cleaning Solvent	(±)

Available in 5 and 10 litre containers

Application Range

Color+ Series QJ inks are recommended for a wide range of uncoated materials. Main applications include:

- Billboards
- Display POP
- Posters
- Indoor and outdoor signage
- Bus shelters
- Taxi advertising
- Exhibition and window graphics

Color+ Series QJ can be used to decorate a wide range of flexible and semi-rigid substrates such as:

- PVC
- Self-adhesive vinyl
- Synthetic papers
- Paper
- Blue backed poster paper

THE END USER MUST DETERMINE THE SUITABILITY OF THIS PRODUCT FOR THE INTENDED USE PRIOR TO PRODUCTION.

Drying

Color+ Series QJ inks have been formulated to meet the drying specification of the Turbojet super wide format presses using solvent-based inks.

The actual drying speed will depend on a number of factors. These include, ink thickness, substrate choice and the print speed.

Colour and Outdoor Durability

The highest quality pigments have been chosen for their super-wide colour gamut maximising the range of colours achievable.

To maximise outdoor durability it is recommended to use full colour CMYK colours in accordance with current industry best practice. Under best practice conditions, accelerated weathering tests have been carried out in a Xenon Arc Weatherometer set to the SAEJ 1960 Standard. Under these conditions, the accelerated weathering of Color+ Series QJ inks equates to approximately 12 months outdoor exposure in a temperate climate such as the UK.

Chemical and Abrasion Resistance

Color+ Series QJ inks have good chemical and abrasion resistance. However, for optimum resistance it is recommended to over-varnish or laminate prints to protect the surface from chemical attack.

Plastics

Certain plastics may be impregnated with lubricants, which may impair adhesion and block resistance even a considerable period of time after printing.

Storage

Color+ Series QJ inks should not be stored in direct sunlight or near heat sources and should be kept away from peroxides. In the interest of maximum shelf life storage temperatures should be between 5°C and 30°C. When stored under these conditions the inks are

expected to have a shelf-life of 12 months from date of manufacture.

Fujifilm Speciality Ink Systems Limited:

- Has certification to the International Environmental Standard, ISO 14001.
- Has certification to the Quality Management Standard, ISO 9001.
- Has certification to the Occupational Health and Safety Standard, ISO 18001.
- Is committed to minimising the risk to users of our products, and also to minimising the impact of our activities on the environment, from formulation through to production and supply.
- Research and development team, work to an in house Health Safety and Environmental policy, termed 'Design for Health, Safety and Environment', with the aim of proactively developing products with the least impact on health, safety and the environment.
- Regularly review and monitor our impacts and activities, setting objectives and targets as part of a continual improvement process.
- Is committed to reducing waste through better use of raw materials, energy, water, re-use and recycling.

Safety and Handling

Color+ Series QJ inks:

- Are formulated to be free from any chemicals toxic to health, carcinogenic, mutagenic or reprotoxic according to Directive 67/548/EC.
- Products marked (≠) are formulated to comply with EN71, but are not routinely tested for compliance with the standard.
- For optimum shelf life, all products should be stored at moderate temperatures, between 5°C and 30°C. Storage outside of these temperatures may lead to deterioration in the performance of the product.

Comprehensive information on the safety and handling of Color+ inks is given in the appropriate Safety Data Sheets.

Environmental Information

Color+ Series QJ inks:

- Do not contain ozone-depleting chemicals as described in the Montreal Convention.
- Are formulated free from aromatic hydrocarbons.

The information and recommendations contained in this Product Information sheet, as well as technical advice otherwise given by representatives of Fujifilm Speciality Ink Systems Limited and its associated companies, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products and because manufacturing methods, printing stocks and other materials vary. For the same reason our products are sold without warranty and on condition that users shall make their own tests to satisfy themselves that they will meet fully their particular requirements. Our policy of continuous product improvement might make some of the information contained in this Product Information sheet out of date and users are requested to ensure that they follow current recommendations.

FUJIFILM SPECIALITY INK SYSTEMS LIMITED

Pysons Road, Broadstairs
Kent CT10 2LE
United Kingdom
T: +44 (0)1843 866668
F: +44 (0)1843 872184
www.fujifilm.eu