

## Fujitrans

Equipment		Software	Calibration data			
Brand	Name		LUT + Target density RGB	Basic calibration ymcd	Intermittance rgb	Thickness
			Trans			
ZBE Chromira	SE, Pro Lab, R2R		3.25 / 3.30 / 3.25	n.a.	n.a.	n.a
Polielettronica	Laserlab 50/76/127		Printer defines own and highest possible Dmax settings (exposure vs chemistry relation)			
Durst	Epsilon		3.25 / 3.30 / 3.25	0.000 / 0.060 / 0.193 / 0.921		n.a
	Zeta					n.a
	Theta 50/51					n.a
	Theta 76/76HS			0.00 / 0.60 / 1.93 / 0.921		n.a
	Lambda			3.30 / 3.40 / 3.30	63.92 / 4.45 / 0.00 / 128.20	
OCE Lightjet	430 / 500XL / 5000		Media target can be downloaded from the Fujifilm Europe .eu website			

All recommended Dmax values can only be reached when using high active chemistry equal to Fujifilm CPRA Digital Pro AC  
 For competitive and recycling chemistry the Dmax should be reduced with -0.10 density

\* Media target location: [http://products.fujifilm.eu/support/color\\_management/photographic/oce.html](http://products.fujifilm.eu/support/color_management/photographic/oce.html)

\* Profiles location : [http://products.fujifilm.eu/support/color\\_management/photographic/](http://products.fujifilm.eu/support/color_management/photographic/)